

DuoLINE HE

AMAZON

DISPOSABLE HIGH EFFICIENCY FILTER BAGS



DuoLINE filter bags have been designed to provide effective filtration for a wide range of applications using a variety of graded filter media.

DuoLINE HE bags utilise multi layered polypropylene microfibre media with built in pre-filter layers. The progressive density depth filtration delivers high efficiency of up to 99.9% positive and controlled solids removal. The multi layered construction of the **HE** Bag uses varying thickness of media to create a depth type filter with up to 12 different grades of material.

Two bag diameters are available in the **DuoLINE HE** range, 4¼ and 7" both fitted as standard with a top ring locator in various materials and styles.

Product Features

- Polypropylene melt blown media, rated between 0.5 - 25µm
- High efficiency media for critical applications

All **DuoLINE** bags are designed to filter from the inside to out leaving the contamination inside the bag for simple disposal.

Amazon Filters manufacture a comprehensive range of filter housings for the **DuoLINE** bags. Available in many materials and sizes to suit all flow rates, please consult our sales office for further details of the full range.

* Verified by independent laboratory testing using latex beads yielding efficiencies up to 99.9% under controlled laboratory conditions.



**Multiple layers
for effective
progressive
filtration**

DUOLINE HE FEATURES AND BENEFITS

- Micron ratings available from 0.5 to 25µm for wide ranging filtration needs
- Optional moulded polypropylene flange with handles for superior sealing and ease of handling
- Wide selection of filter media and support ring materials
- Identification supplied with every bag
- Silicone free for use in automotive paint applications

DUOLINE HE

TECHNICAL DATA

Maximum Operating Conditions

Temperature 19HE: 80°C

Recommended Maximum Differential Pressure: 4 Bar

Filtration Efficiency

0.5µm:	99.0%
1µm:	99.0%
5µm:	99.3%
10µm:	99.8%
25µm:	99.9%

Dimensional Data

Bag Size	Length (mm)	Ring Diameter (mm)	Capacity (Litres)	Surface Area (m ²)	Flow Rate (m ³ /hr) *1
1M (P3)	200	108	1.8	0.068	1
2M (P4)	355	108	3.2	0.120	2
1G (P1)	420	178	10.0	0.235	4
2G (P2)	810	178	20.0	0.453	8

*1The flow rates quoted are our maximum recommended values for 5µm bag type based on water, or liquid of a similar viscosity at ambient temperature. For advice on the filtration of liquids with greater viscosities please contact our sales office.

ORDERING GUIDE

19

All bags are available with an optional nylon Monofilament outer support scrim - please refer to the Sales Office.

Example: 19HE025-2GTEP = High Efficiency polypropylene Meltblown media, 25µm rating, Double length, 7" diameter, Stainless steel support ring with loops, Silicone free

INDUSTRIES AND APPLICATIONS

Pharmaceutical	• Bulk transfer, Catalyst removal, Powder trap
Cosmetics	• Creams, Lotions, Gels, Filling head trap filter
Metal Finishing	• Wash solutions, Paints, Resins, Varnishes
Water Treatment	• Membrane protection (Reverse osmosis, nano), Resin trap, Potable water
Automotive	• Cooling fluid, Electrophoretic paints, Degreasing systems, Phosphate filter

AMAZON FILTERS LTD.

ALBANY PARK ESTATE, FRIMLEY ROAD,
CAMBERLEY, SURREY, GU16 7PG
ENGLAND

Tel: +44 (0) 1276 670 600

Fax: +44 (0) 1276 670 101

Email: sales@amazonfilters.co.uk

Web: www.amazonfilters.co.uk



Certificate No. FM39584

Distributed by: